

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Spartan Chemical Company, Inc.

Product Name or Number (as it appears on label):

Product Division: **Janitorial**

WHITE SUN

1110 Spartan Drive Maumee OH 43537

Product Number: 4050

Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Non Hazardous Products

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: *1 - Slight; Chronic Hazard
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
· ·	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Table Z-1-A

Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Acrylic polymer	10-15	Proprietary	Not Established	Not Established	Not Established	No
Tributoxyethyl phosphate	1-5	78-51-3	Not Established	Not Established	Not Established	No
Styrene/Acrylic copolymer	1-5	Proprietary	Not Established	Not Established	Not Established	No
*Diethylene glycol monoethyl	1-5	111-90-0	140 (AIHA)	Not Established	Not Established	No
ether Commont: *This substance is sub-	-	-	`- ′	-	-	-

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

	Boiling Point: 212 °F	Vapor Pressure:	Unknown
Ξ	Vapor Density (AIR = 1): Unknown	Solubility in Water:	Complete
	pH: 8.0-9.0	Specific Gravity (H ₂ O=1):	1.029
	Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	17-19
	Physical State: Liquid		
	Appearance & Odor: Translucent emulsion, ammoniacal odor		

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 210 °F	Method Used: ASTM-D56		
Flammable Limits: N/A	Flame Extension: N/A		
Extinguishing Media: N/A			
Special Fire Fighting Procedures: N/A			
Unusual Fire & Explosive Hazards: N/A			

SECTION V: HEALTH HAZARD DATA Threshold Limit Value: Not Established Primary Routes of Entry: Inhalation, Skin Contact, Eyes Effects of Overexposure- Causes mild eye irritation: Symptoms may include pain, redness, swelling and tearing. Conditions to Avoid: May cause skin irritation: Symptoms may include redness, pain and swelling. Harmful if swallowed: Symptoms may include nausea, vomiting, pain and diarrhea. Inhalation of vapors may cause respiratory irritation, headache and nausea. Contains diethylene glycol monoethyl ether which may cause central nervous system depression, liver and kidney impairment. Contains tributoxyethyl phosphate which may cause nervous system effects such as ataxia, breathing abnormalities and tremors with prolonged or repeated contact. Avoid contact with eyes and skin. Avoid breathing product vapors or mist. Use with adequate ventilation. Do not taste or swallow. Wash thoroughly after handling. Conditions Aggravated by Use: Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis. **Emergency & First Aid Procedures:** Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical Skin: Remove contaminated clothing. Flush skin thoroughly with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse. Ingestion: Do not induce vomiting unless told to do so by medical personnel. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person. Inhalation: Move person to fresh air. If irritation persists get medical attention. SECTION VI: REACTIVITY DATA Stability: Stable Incompatible Materials: None known

SECTION VII: SPILL OR LEAK PROCEDURES

Hazardous Decomposition Products: None known

Steps to be Taken in Case

Material is Released or Spilled: Small spills may be flushed with water to sanitary sewer system. Dike and contain large spill with inert

material and transfer liquid to containers for recovery or disposal. Follow all federal, state and local

Hazardous Polymerization: Will Not Occur

regulations. Do not discharge into streams, lakes or other surface waters.

Waste Disposal Method: Incineration or approved landfill.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not usually required when good general ventilation is provided. However if exposure levels are exceeded

(see Section II) or if respiratory irritation occurs, use of a NIOSH approved respirator suitable for the

conditions of use and chemicals listed in Section II should be considered.

Ventilation: Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.

Protective Gloves(Specify Type): Rubber or other impervious gloves are recommended.

Splash goggles are recommended to prevent eye contact. Eye Protection(Specify Type):

Other Protective Equipment: See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep from freezing.

Other Precautions: Keep out of reach of children.

© SCC 01/09/2012 Name: Title: Ronald T. Cook Manager, Regulatory Affairs

Effective Date: 01/09/2012 Supercedes: 09/22/2088 WHITE SUN

Ref: 29 CFR 1910.1200 (OSHA) Changes: General review

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.